

# PANEL SANITARIO FM FIBER MINERAL FIRE RESISTANT



# **B-HYGIENIC HYGIROCK SANDWICH PANEL**

#### CHARACTERISTICS FRP
































- Food safe (HACCP, EU, BRC, FDA, USDA, ...)
- Economical (less cleaning product is needed)
- Chemically resistant (e.g. blood, acids, brine, milk, ...)
- Water- and dirt resistant and anti-fungal
- High impact- and scratch proof
- Easily and simply cleanable
- Quick and easy to install (modular system)
- Suitable for heated and cooled spaces
- Fire retardant (optional, standard Euroclass E)
- Anti-graffiti (ideal for public spaces)
- Does't discolour and doesn't take in smells
- Non corrosive
- If necessary, easy reparable
- Available in all RAL colours (standard RAL 9010 = hygienic white)



#### PRODUCT DESCRIPTION

The B-Hygienic sandwich panel with rockwool core is used where high demands are made on fire resistance. The rockwool core has a Euroclass A2-s1,d0 certificate. The panel is available with both sides B-Hygienic FRP polyester smooth or embossed as onesided B-Hygienic FRP and on the other side galvanized steel with or without a coating. The joint between the panels can be closed with profiles, or optional seamless with the unique B-Hygienic HygiSeal product.

# TECHNICAL INFORMATION ROCKWOOL

The rockwool fibers are vertically structured so that high pressure and shear forces can be absorbed.

Rockwool, non-flammable with Euroclass A2-s1,d0 certificate:

Density: 125 kg/m3

Compressive strain: 110 kPa

Thermal conductivity classification: 045 Thermal conductivity: 045 W(mK) Specific heat capacity: 0,84 kJ(kgK) Moisture behavior: continuous waterproof Water vapor diffusion resistance: 1,4µ

# TECHNICAL INFORMATION FRP

Standard Euroclass E Optional Euroclass C-s3,d0 or B-s3,d0

Smooth surface (2 mm) or embossed (2,3 mm)

### DIMENSIONS

Width: 1200 mm

Length: according to specifications

# APPLICATIONS

Food industry

Restaurants & kitchens

Cleanrooms

Public buildings with high hygienic requirements such as hospitals, schools, stations,

Pharmaceutical plants Chemical Industry

## CONNECTION

The panels are supplied with loose tongue consisting of fiberglass reinforced plaster.

Finishing polyester compound:

- Standard with PVC H-profile
- Optional B-Hygienic Hygiseal seamless finish





Maesbossen 3B | 9160 Lokeren | Belgium

Telf. Directo desde el Exterior: +51 - 994707273 Fijo: +51 - 234-1864

E-mail: inro@b.hygienicperu.com / www.b-hygienicperu.com

Panamerica Sur Km. 18 Mz. Lote 18 - S.J.M.

Perú - Latin America -

